



Classes and Objects; Inheritance

# OOP, Defining a Class

- Python was built as a procedural language
  - OOP exists and works fine, but feels a bit more "tacked on"
  - Java probably does classes better than Python (gasp)
- Declaring a class:

```
class name:  
    statements
```

# Fields

## **name = value**

- Example:

```
class Point:  
    x = 0  
    y = 0
```

```
# main  
p1 = Point()  
p1.x = 2  
p1.y = -5
```

- can be declared directly inside class (as shown here) or in constructors (more common)
- Python does not really have encapsulation or private fields
  - relies on caller to "be nice" and not mess with objects' contents

### point.py

```
1 class Point:  
2     x = 0  
3     y = 0
```

# Using a Class

import **class**

- client programs must import the classes they use

## point\_main.py

```
1 from Point import *
2
3 # main
4 p1 = Point()
5 p1.x = 7
6 p1.y = -3
7 ...
8
9 # Python objects are dynamic (can add fields any time!)
10 p1.name = "Tyler Durden"
```

# Object Methods

```
def name(self, parameter, ..., parameter) :  
    statements
```

- `self` *must* be the first parameter to any object method
  - represents the "implicit parameter" (`this` in Java)
- *must* access the object's fields through the `self` reference

```
class Point:
```

```
    def translate(self, dx, dy):
```

```
        self.x += dx
```

```
        self.y += dy
```

```
    ...
```

# "Implicit" Parameter (`self`)

- Java: `this`, `implicit`

```
public void translate(int dx, int dy) {  
    x += dx;          // this.x += dx;  
    y += dy;          // this.y += dy;  
}
```

- Python: `self`, `explicit`

```
def translate(self, dx, dy):  
    self.x += dx  
    self.y += dy
```

- Exercise: Write `distance`, `set_location`, and `distance_from_origin` methods.

# Exercise Answer

## point.py

```
1  from math import *
2
3  class Point:
4      x = 0
5      y = 0
6
7      def set_location(self, x, y):
8          self.x = x
9          self.y = y
10
11     def distance_from_origin(self):
12         return sqrt(self.x * self.x + self.y * self.y)
13
14     def distance(self, other):
15         dx = self.x - other.x
16         dy = self.y - other.y
17         return sqrt(dx * dx + dy * dy)
```

# Calling Methods

- A client can call the methods of an object in two ways:
  - (the value of `self` can be an implicit or explicit parameter)
- 1) **object.method(parameters)**  
or
- 2) **Class.method(object, parameters)**
- Example:

```
p = Point(3, -4)
p.translate(1, 5)
Point.translate(p, 1, 5)
```

# Constructors

```
def __init__(self, parameter, ..., parameter):  
    statements
```

- a constructor is a special method with the name `__init__`
- Example:

```
class Point:  
    def __init__(self, x, y):  
        self.x = x  
        self.y = y  
    ...
```

- How would we make it possible to construct a `Point()` with no parameters to get `(0, 0)`?

# toString and `__str__`

```
def __str__(self):  
    return string
```

- equivalent to Java's `toString` (converts object to a string)
- invoked automatically when `str` or `print` is called

Exercise: Write a `__str__` method for `Point` objects that returns strings like `"(3, -14)"`

```
def __str__(self):  
    return "(" + str(self.x) + ", " + str(self.y) + ")"
```

# Complete Point Class

## point.py

```
1 from math import *
2
3 class Point:
4     def __init__(self, x, y):
5         self.x = x
6         self.y = y
7
8     def distance_from_origin(self):
9         return sqrt(self.x * self.x + self.y * self.y)
10
11    def distance(self, other):
12        dx = self.x - other.x
13        dy = self.y - other.y
14        return sqrt(dx * dx + dy * dy)
15
16    def translate(self, dx, dy):
17        self.x += dx
18        self.y += dy
19
20    def __str__(self):
21        return "(" + str(self.x) + ", " + str(self.y) + ")"
```



# Generating Exceptions

```
raise ExceptionType ("message")
```

- useful when the client uses your object improperly
- types: `ArithmeticError`, `AssertionError`, `IndexError`, `NameError`, `SyntaxError`, `TypeError`, `ValueError`
- Example:

```
class BankAccount:  
    ...  
    def deposit(self, amount):  
        if amount < 0:  
            raise ValueError("negative amount")  
        ...
```

# Inheritance

```
class name (superclass) :  
    statements
```

- Example:

```
class Point3D(Point) :      # Point3D extends Point  
    z = 0  
    ...
```

- Python also supports *multiple inheritance*

```
class name (superclass, ..., superclass) :  
    statements
```

(if > 1 superclass has the same field/method, conflicts are resolved in left-to-right order)

# Calling Superclass Methods

- methods: **class.method(object, parameters)**
- constructors: **class.\_\_init\_\_(parameters)**

```
class Point3D(Point):  
    z = 0  
    def __init__(self, x, y, z):  
        Point.__init__(self, x, y)  
        self.z = z  
  
    def translate(self, dx, dy, dz):  
        Point.translate(self, dx, dy)  
        self.z += dz
```